


Steel Pipe


| Code # | Description | Size |
|--------|-------------|------|
|--------|-------------|------|



SCH-40 Black Threaded & Coupled

Cont. Weld A120/A53F GR A; 21 Foot Lengths


| | | |
|--------|---------------------------------|--------|
| 1-0520 | SCH-40 Black Threaded & Coupled | 1/2" |
| 1-0525 | SCH-40 Black Threaded & Coupled | 3/4" |
| 1-0530 | SCH-40 Black Threaded & Coupled | 1" |
| 1-0535 | SCH-40 Black Threaded & Coupled | 1-1/4" |
| 1-0540 | SCH-40 Black Threaded & Coupled | 1-1/2" |
| 1-0545 | SCH-40 Black Threaded & Coupled | 2" |



SCH-40 Galvanized Threaded & Coupled

Cont. Weld A120/A53F GR A; 21 Foot Lengths


| | | |
|--------|--------------------------------------|--------|
| 1-1120 | SCH-40 Galvanized Threaded & Coupled | 1/2" |
| 1-1125 | SCH-40 Galvanized Threaded & Coupled | 3/4" |
| 1-1130 | SCH-40 Galvanized Threaded & Coupled | 1" |
| 1-1135 | SCH-40 Galvanized Threaded & Coupled | 1-1/4" |
| 1-1140 | SCH-40 Galvanized Threaded & Coupled | 1-1/2" |
| 1-1145 | SCH-40 Galvanized Threaded & Coupled | 2" |



SCH-40 Black Plain End Beveled

Beveled Cont. Weld A120/A53F GR A; 21 Foot Lengths

| | | |
|--------|--------------------------------|--------|
| 1-1720 | SCH-40 Black Plain End Beveled | 1/2" |
| 1-1725 | SCH-40 Black Plain End Beveled | 3/4" |
| 1-1730 | SCH-40 Black Plain End Beveled | 1" |
| 1-1735 | SCH-40 Black Plain End Beveled | 1-1/4" |
| 1-1740 | SCH-40 Black Plain End Beveled | 1-1/2" |
| 1-1745 | SCH-40 Black Plain End Beveled | 2" |



SCH-80 Black Plain End Beveled

Cont. Weld A120/A53F GR A; 21 Foot Lengths

| | | |
|--------|--------------------------------|--------|
| 1-3020 | SCH-80 Black Plain End Beveled | 1/2" |
| 1-3025 | SCH-80 Black Plain End Beveled | 3/4" |
| 1-3030 | SCH-80 Black Plain End Beveled | 1" |
| 1-3035 | SCH-80 Black Plain End Beveled | 1-1/4" |
| 1-3040 | SCH-80 Black Plain End Beveled | 1-1/2" |



CONTINUOUS WELD STANDARD AND LINE PIPE DATA

| Size, Inches Nominal OD | Wall Thickness, Inches | Nominal Weight Lbs./Ft. | | | Class | Mill Test* Pressure psi | Calculated Internal Pressure at Min. Yield Strength psi | | Calculated Ultimate Bursting Pressure+ psi | | Size, Inches | | |
|----------------------------|------------------------------|----------------------------|------------------------------|--------------------------|-------|----------------------------------|--|----------|--|----------|-----------------|-------|-------|
| | | Plain End | T & C | | | | Class I | Class II | Class I | Class II | OD | Nom. | |
| | | | Standard Pipe Coupling | Line Pipe Coupling | | | | | | | | | O.H. |
| 1/8 | 0.405 | 0.068 | 0.24 | 0.24 | 0.25 | Std. | 700 | 8400 | 9400 | 15120 | 16120 | 0.405 | 1/8 |
| | | 0.095 | 0.31 | - | 0.32 | XS | 850 | 11730 | 13130 | 21120 | 22520 | | |
| 1/4 | 0.540 | 0.088 | 0.42 | 0.42 | 0.43 | Std. | 700 | 8150 | 9130 | 14070 | 15050 | 0.540 | 1/4 |
| | | 0.119 | 0.54 | - | 0.54 | XS | 850 | 11020 | 12330 | 19830 | 21150 | | |
| 3/8 | 0.675 | 0.091 | 0.57 | 0.57 | 0.57 | Std. | 700 | 6730 | 7550 | 12130 | 12930 | 0.675 | 3/8 |
| | | 0.126 | 0.74 | - | 0.74 | XS | 850 | 9330 | 10450 | 16800 | 17920 | | |
| 1/2 | 0.840 | 0.109 | 0.85 | 0.85 | 0.86 | Std. | 700 | 6480 | 7270 | 11680 | 12450 | 0.840 | 1/2 |
| | | 0.147 | 1.09 | - | 1.09 | XS | 850 | 8750 | 9800 | 15750 | 16800 | | |
| 3/4 | 1.050 | 0.113 | 1.13 | 1.13 | 1.14 | Std. | 700 | 5380 | 6030 | 9680 | 10340 | 1.050 | 3/4 |
| | | 0.154 | 1.47 | - | 1.48 | XS | 850 | 7330 | 8220 | 13200 | 14080 | | |
| | | 0.308 | 2.44 | - | - | XXS | 1000 | - | - | - | - | | |
| 1 | 1.315 | 0.133 | 1.68 | 1.68 | 1.70 | Std. | 700 | 5050 | 5670 | 9100 | 9720 | 1.315 | 1 |
| | | 0.179 | 2.17 | - | 2.18 | XS | 850 | 6800 | 7620 | 12250 | 13070 | | |
| | | 0.358 | 3.66 | - | - | XXS | 1000 | - | - | - | - | | |
| 1-1/4 | 1.660 | 0.140 | 2.27 | 2.28 | 2.30 | Std. | 1000 | 4220 | 4720 | 7580 | 8100 | 1.660 | 1-1/4 |
| | | 0.191 | 3.00 | - | 3.02 | XS | 1300 | 5750 | 6450 | 10350 | 11050 | | |
| | | 0.382 | 5.21 | - | - | XXS | 1400 | - | - | - | - | | |
| 1-1/2 | 1.90 | 0.145 | 2.72 | 2.73 | 2.75 | Std. | 1000 | 3820 | 4270 | 6870 | 7330 | 1.900 | 1-1/2 |
| | | 0.200 | 3.63 | - | 3.66 | XS | 1300 | 5270 | 5900 | 9470 | 10100 | | |
| | | 0.400 | 6.41 | - | - | XXS | 1400 | - | - | - | - | | |
| 2 | 2.375 | 0.154 | 3.65 | 3.68 | 3.75 | Std. | 1000 | 3230 | 3630 | 5830 | 6230 | 2.375 | 2 |
| | | 0.218 | 5.02 | - | 5.07 | XS | 1300 | 4580 | 5130 | 8270 | 8820 | | |
| 2-1/2 | 2.875 | 0.203 | 5.79 | 5.82 | 5.90 | Std. | 1000 | 3533 | 3950 | 6350 | 6780 | 2.875 | 2-1/2 |
| | | 0.276 | 7.66 | - | 7.73 | XS | 1300 | 4800 | 5380 | 8360 | 9220 | | |
| 3 | 3.500 | 0.156 | 5.57 | - | - | - | - | - | - | - | - | 3.500 | 3 |
| | | 0.188 | 6.63 | - | - | - | 1000 | 2680 | 3000 | 4830 | 5150 | | |
| | | 0.216 | 7.58 | 7.62 | 7.70 | Std. | 1000 | 3080 | 3450 | 5550 | 5920 | | |
| | | 0.300 | 10.25 | - | 10.3 | XS | 1300 | 4280 | 4800 | 7720 | 8230 | | |
| 3-1/2 | 4.000 | 0.188 | 7.63 | - | - | - | 1200 | 2350 | 2630 | 4230 | 4520 | 4.000 | 3-1/2 |
| | | 0.226 | 9.11 | 9.20 | 9.25 | Std. | 1200 | 2830 | 3170 | 5080 | 5420 | | |
| | | 0.318 | 12.51 | - | 12.63 | XS | 1700 | 3970 | 4450 | 7150 | 7630 | | |
| 4 | 4.500 | 0.156 | 7.25 | - | - | - | 1000 | 1730 | 1940 | 3120 | 3330 | 4.500 | 4 |
| | | 0.188 | 8.64 | - | - | - | 1200 | 2080 | 2330 | 3770 | 4020 | | |
| | | 0.219 | 10.00 | - | - | - | 1200 | - | - | - | - | | |
| | | 0.237 | 10.79 | 10.89 | 11.00 | Std. | 1200 | 2630 | 2950 | 4730 | 5050 | | |
| | | 0.337 | 14.98 | - | 15.17 | XS | 1700 | 3750 | 4200 | 6730 | 7180 | | |

* Mill test pressures are standard USS test pressures which equal or exceed specification test procedures.
 + Calculated pressure values are calculated on basis of minimum yield strength, minimum ultimate strength and nominal dimensions specified by API and ASTM.
 Note: Inquire for further information on ASTM A589 covering water well pipe and WWP-404 & WW-P-406b covering continuous weld pipe to federal specifications.